

Type 27 & 28 Wheel Grinders

Cleco®

1200 Vertical Series

Nominal Motor Power

2.0 - 2.2 hp

1.5 - 1.6 kW

- Governed
- Lock-Off Lever Throttle



1260DVL-07

Model Number	Free Speed rpm	Max. Power		Weight w/Guard		Height		Type 27 & 28 Wheel Capacity	Wheel Guard Size
		hp	kw	lbs.	kg	in.	mm		
1200 Series									
1260DVL-07	6,000	2.0	1.5	7.5	3.4	7.5	191	7"	7"
1277DVL-07	7,700	2.2	1.6	7.5	3.4	7.5	191	7"	7"

GENERAL:

Air Inlet: 1/2" NPT

Minimum Hose Size: 1/2"

Tool performance rated @ 90psi (620 kPa) air pressure.

Refer to page 7 for description of Rapid Select.

STANDARD EQUIPMENT:

Operating instructions & service manual

Wheel Guard & Spindle Wrench

OPTIONAL EQUIPMENT:

Wheel Guards: Page 41

Additional Accessories: Pages 41-43

WARNING: Face & eye protection must be worn while operating power tools, per ANSI B186.1. Cutting tool maximum speed rating must equal or exceed speed of air tool @ 90psi (620 kPa). Follow cutting tool manufacturer's mounting & operating instructions.