

Uncompromising Cordless Power.

All cordless tools offer easy-working freedom from electrical cords and air hoses—but most can't deliver the hardworking power needed to get the tough jobs done. The Ingersoll Rand IQ^{v20} Series™ of 20-volt tools is different: each is designed, built and tested to stand up to the all day, every day demands of professionals. With 20 volts of hard-hitting, long-lasting power, IQ^{v20} Series tools deliver uncompromising abilities to **Do the Job, Do it Fast, Do it Every Time.**

Performance:

 With 20 volts of lithium-ion power, IQ^{v20} Series tools offer torque and speed advantages comparable to premium-quality air tools.

Versatility:

 No cord or air hose means go-anywhere versatility even in tight spots.

Durability:

 Strength in every detail, including robust, metal-reinforced composite housings that protect against breakage and corrosive chemicals.





















One Battery Platform. Multiple Benefits.

Ingersoll Rand's BC1121 lithium-ion universal charger gets all of the batteries in our IQV12 and IQV20 Series* lineup charged and ready to go whenever you are. Whether it's our 20V or 12V batteries, this innovative, multi-use battery charger will make it easier and faster to have a freshly charged battery to get your work done now, not later.



offer triple battery protection, prevent over loading, over charging and over discharging for

longer tool and battery life.

IQ^{V20} Series[™] High-Torque Impactool[™]

W7150 1/2"

Tuned impact mechanism

delivers more torque, is more durable and more efficient; 780 ft-lb max torque and 1,100 ft-lb nut-busting torque equals the output of our 2135TiMAX air Impactool—all from a 6.8-lb tool/battery combo



is designed to be strong and lightweight, while protecting interior components

All-metal drivetrain and hammer mechanism is robust. durable and optimized for maximum power and efficiency

Variable-speed switch provides maximum control of the tool



automotive repair



Heavy equipment






Best-in-class power-to-weight ratio

High-power rare earth magnet (neodymium) motor offers a long life and high power

Patent-pending soft touch over-molded grip minimizes vibration, reduces fatigue and enhances user comfort during extended use

Tough composite housing and patented steel-reinforced frame protects against fluids, chemicals and repeated drops



| IQ ^{V20} Serie | s™ Impactool™ | | | | | | | | |
|-------------------------|---------------|---------------|----------------------------|-----------------------|-------------------------|-------------------------------------|------------------------------|-----------------------------|------------------------------|
| Model | Battery | Voltage DC | Drive Size, Type | Impacts per Minute | No-Load Speed rpm | Nut-Busting Torque ft-Ib (Nm) | Max. Torque ft-lb (Nm) | Tool & Weight Ib (kg) | Battery Length in (mm) |
| W7150 | BL2010/BL2022 | 20 | 1/2", Hog Ring | 2,300 | 0-1,900 | 1,100 (1,491) | 780 (1,057) | 6.8 (3.1) | 9.4 (238) |
| W7150P | BL2010/BL2022 | 20 | 1/2", Pin Detent | 2,300 | 0-1,900 | 1,100 (1,491) | 780 (1,057) | 6.9 (3.1) | 9.4 (238) |
| W7250 | BL2010/BL2022 | 20 | 1/2", 2" Extended Hog Ring | 2,300 | 0-1,900 | 1,100 (1,491) | 780 (1,057) | 6.9 (3.1) | 11.2 (285) |



| Model | Description |
|------------|---|
| W7150-K1 | 1/2" Impactool, Charger, 1 BL2010 Li-ion Battery & Case |
| W7150-K2 | 1/2" Impactool, Charger, 2 BL2010 Li-ion Batteries & Case |
| W7150-K12 | 1/2" Impactool, Charger, 1 BL2022 Li-ion Battery & Case |
| W7150-K22 | 1/2" Impactool, Charger, 2 BL2022 Li-ion Batteries & Case |
| W7150P-K12 | 1/2" Pin Impactool, Charger, 1 BL2022 Li-ion Battery & Case |
| W7150P-K22 | 1/2" Pin Impactool, Charger, 2 BL2022 Li-ion Batteries & Case |
| W7250-K1 | 1/2" Impactool, Charger, 1 BL2010 Li-ion Battery & Case |
| W7250-K2 | 1/2" Impactool, Charger, 2 BL2010 Li-ion Batteries & Case |

IQ^{V20} Series[™] Right Angle Impactool[™]

W5330 3/8" & W5350 1/2"



| IQ ^{∨20} <i>Series</i> ™ Right Angle I | mpactool™ | | | | | | |
|---|---------------|---------------|---------------------|----------------------|--------------------------|-------------------|-------------------|
| | | | | | | Tool & Battery | |
| Model | Battery | Voltage DC | Drive Size, Type | No-Load Speed rpm | Max Torque ft-lb (Nm) | Weight lb (kg) | Length in (mm) |
| W5330 | BL2012 | 20 | 3/8", Hog Ring | 0-1,900 | 180 (245) | 4.55 (2.06) | 17.25 (439) |
| W5330 | BL2010/BL2022 | 20 | 3/8", Hog Ring | 0-1,900 | 190 (258) | 5.15 (2.27) | 17.25 (439) |
| W5350 | BL2012 | 20 | 1/2", Hog Ring | 0-1,900 | 180 (245) | 4.55 (2.06) | 17.25 (439) |
| W5350 | BL2010/BL2022 | 20 | 1/2", Hog Ring | 0-1,900 | 190 (258) | 5.15 (2.27) | 17.25 (439) |



| Model | Description |
|-----------|---|
| W5330-K12 | 3/8" Impactool, Charger, 1 BL2012 Li-ion Battery & Case |
| W5330-K22 | 3/8" Impactool, Charger, 2 BL2012 Li-ion Batteries & Case |
| W5350-K12 | 1/2" Impactool, Charger, 1 BL2012 Li-ion Battery & Case |
| W5350-K22 | 1/2" Impactool, Charger, 2 BL2012 Li-ion Batteries & Case |

IQ^{V20} Series[™] Mid-Torque Impactool[™]


W5110 1/4", W5130 3/8" & W5150 1/2"

Tuned impact mechanism

delivers 190 ft-lb of torque from a lightweight, balanced, compact tool that measures just 6.6" long from tip to tail

Durable, steel-lined aluminum hammer case is designed to be strong and lightweight, while protecting interior components for a long lifetime of durability

Variable-speed switch with electronic brake provides maximum control of the tool and increases safety—depress trigger, drive stops spinning



Tough composite housing and patented steel-reinforced frame protects against fluids, chemicals and repeated drops

Lightweight, balanced, ergonomic handle with patent-pending rubber over-molded **grip** minimizes vibration, reduces fatigue and enhances user comfort during extended use

Ideal for:







Facilities



General

| IQ ^{∨20} Series™ Imp | oactool™ | | | | | | | |
|-------------------------------|---------------|---------------|---------------------|-----------------------|----------------------|-----------------------------|-------------------------------|------------------------------|
| Model | Battery | Voltage DC | Drive Size, Type | Impacts per Minute | No-Load Speed rpm | Max Torque ft-lb (Nm) | Tool & I Weight Ib (kg) | Battery Length in (mm) |
| W5110 | BL2012 | 20 | 1/4", Hex | 2,900 | 0-1,700 | 165 (225) | 3.6 (1.6) | 6.6 (168) |
| W5110 | BL2010/BL2022 | 20 | 1/4", Hex | 2,900 | 0-1,700 | 175 (240) | 4.1 (1.9) | 6.6 (168) |
| W5130 | BL2012 | 20 | 3/8", Hog Ring | 2,900 | 0-1,700 | 180 (245) | 3.6 (1.6) | 6.6 (162) |
| W5130 | BL2010/BL2022 | 20 | 3/8", Hog Ring | 2,900 | 0-1,700 | 190 (260) | 4.1 (1.9) | 6.6 (162) |
| W5150 | BL2012 | 20 | 1/2", Hog Ring | 2,900 | 0-1,700 | 180 (245) | 3.6 (1.6) | 6.6 (162) |
| W5150 | BL2010/BL2022 | 20 | 1/2" ,Hog Ring | 2,900 | 0-1,700 | 190 (260) | 4.1 (1.9) | 6.6 (162) |



| Model | Description |
|-----------|---|
| W5110-K12 | 1/4" Hex Impactool, Charger, 1 BL2012 Li-ion Battery & Case |
| W5110-K22 | 1/4" Hex Impactool, Charger, 2 BL2012 Li-ion Batteries & Case |
| W5130-K12 | 3/8" Impactool, Charger, 1 BL2012 Li-ion Battery & Case |
| W5130-K22 | 3/8" Impactool, Charger, 2 BL2012 Li-ion Batteries & Case |
| W5150-K12 | 1/2" Impactool, Charger, 1 BL2012 Li-ion Battery & Case |
| W5150-K22 | 1/2" Impactool, Charger, 2 BL2012 Li-ion Batteries & Case |

IQ^{V20} Series[™] High Cycle Impactool[™]

W5111 1/4", W5131P 3/8" & W5151P 1/2"



Tuned impact mechanism delivers 175 ft-lb of maximum torque, ready to perform job after job

1/4" Hex, 3/8" and 1/2" Pins for maximum versatility and secure and accurate rundowns

Durable, steel-lined aluminum hammer case is designed to protect internal components, while patented metal reinforced housing withstands repeated drops

Fast application speeds help meet plant throughput goals

Compact design makes operation and access easier in tight spots

Ideal for:



Production assembly



All-metal drivetrain and hammer mechanism is robust. durable and optimized for maximum power and efficiency

High-power rare earth magnet (neodymium) motor and replaceable **brushes** offer a long, durable life and high power

Rubber over-molded grip minimizes vibration, reduces fatigue and enhances user comfort during extended use

| IQ ^{V20} Series [™] I | mpactool™ | | | | | | | |
|---|---------------|---------------|---------------------|-----------------------|----------------------|---------------------------|-----------------------------|------------------------------|
| Model | Battery | Voltage DC | Drive Size, Type | Impacts per Minute | No-Load Speed rpm | Max. Torque ft-lb (Nm) | Tool & Weight Ib (kg) | Battery Length in (mm) |
| W5111 | BL2012 | 20 | 1/4", Hex | 2,800 | 0-1,900 | 160 (215) | 3.5 (1.6) | 6.0 (152) |
| W5111 | BL2010/BL2022 | 20 | 1/4", Hex | 2,800 | 0-1,900 | 175 (240) | 4.2 (1.9) | 6.0 (152) |
| W5131P | BL2012 | 20 | 3/8", Pin Detent | 2,800 | 0-1,900 | 160 (215) | 3.5 (1.6) | 5.9 (150) |
| W5131P | BL2010/BL2022 | 20 | 3/8", Pin Detent | 2,800 | 0-1,900 | 175 (240) | 4.2 (1.9) | 5.9 (150) |
| W5151P | BL2012 | 20 | 1/2", Pin Detent | 2,800 | 0-1,900 | 160 (215) | 3.5 (1.6) | 6.1 (154) |
| W5151P | BL2010/BL2022 | 20 | 1/2", Pin Detent | 2,800 | 0-1,900 | 175 (240) | 4.2 (1.9) | 6.1 (154) |



| Model | Description |
|------------|---|
| W5111-K12 | 1/4" Hex Impactool, Charger, 1 BL2012 Li-ion Battery & Case |
| W5111-K22 | 1/4" Hex Impactool, Charger, 2 BL2012 Li-ion Batteries & Case |
| W5131P-K12 | 3/8" Pin Impactool, Charger, 1 BL2012 Li-ion Battery & Case |
| W5131P-K22 | 3/8" Pin Impactool, Charger, 2 BL2012 Li-ion Batteries & Case |
| W5151P-K12 | 1/2" Pin Impactool, Charger, 1 BL2012 Li-ion Battery & Case |
| W5151P-K22 | 1/2" Pin Impactool, Charger, 2 BL2012 Li-ion Batteries & Case |

IQ^{V20} *Series*[™] Ratchet Wrench

R3130 3/8" & R3150 1/2"



| IQ ^{v20} Series [™] Ratchet Wrench | | | | | | | |
|--|---------------|---------|--------------|---------------|-------------|-------------------|-------------------|
| | | Voltage | Drive | No-Load Speed | Max. Torque | | Battery Length |
| Model | Battery | DC | Size, Type | rpm | ft-lb (Nm) | Weight lb (kg) | Length in (mm) |
| R3130 | BL2012 | 20 | 3/8", Square | 0-225 | 54 (73) | 4.4 (2.0) | 17.5 (445) |
| R3130 | BL2010/BL2022 | 20 | 3/8", Square | 0-225 | 54 (73) | 5.0 (2.3) | 17.5 (445) |
| R3150 | BL2012 | 20 | 1/2", Square | 0-225 | 54 (73) | 4.4 (2.0) | 17.5 (445) |
| R3150 | BL2010/BL2022 | 20 | 1/2", Square | 0-225 | 54 (73) | 5.0 (2.3) | 17.5 (445) |



| Model | Description |
|-----------|---|
| R3130-K12 | 3/8" Ratchet, Charger, 1 BL2012 Li-ion Battery & Case |
| R3130-K22 | 3/8" Ratchet, Charger, 2 BL2012 Li-ion Batteries & Case |
| R3150-K12 | 1/2" Ratchet, Charger, 1 BL2012 Li-ion Battery & Case |
| R3150-K22 | 1/2" Ratchet, Charger, 2 BL2012 Li-ion Batteries & Case |

IQ^{V20} *Series*[™] **Drill/Driver**











*Requires 3.0 Ah battery or higher.

| IQ ^{v20} Series™ Drill/Driver | | | | | | | | |
|--|---------------|---------------|---------------------|---------|-----------|----------------------------------|-------------------|-------------------|
| | | | | No-Load | Speed rpm | | Tool & | Battery |
| Model | Battery | Voltage DC | Drive Size, Type | High | Low | Max. Stall Torque in-lbs (Nm) | Weight lb (kg) | Length in (mm) |
| D5140 | BL2010/BL2022 | 20 | 1/2", Chuck | 0-500 | 0-1,900 | 700 (80) | 5.4 (2.45) | 9.25 (235) |



| Model | Description |
|----------|--|
| D5140-K1 | 1/2" Drill/Driver, Charger, 1 BL2010 Li-ion Battery & Case |
| D5140-K2 | 1/2" Drill/Driver, Charger, 2 BL2010 Li-ion Batteries & Case |

IQ^{V20} *Series*[™] Grease Gun

LUB5130

High operating pressure and flow rate powers through clogged fittings, quickly delivering grease and reducing job time Electronic shutdown and high-pressure LED indicator prevents grease spills and extends motor life **Ergonomic handle with comfort grip** helps reduce vibration, fatigue and enhances user comfort

Patent-pending Inline™ battery mount design offers greater portability and easier access



Ideal for:

repeated drops

fluids, chemicals and







Facilities



industria

| IQ ^{v20} Series™ Grease Gun | | | | | | | | | |
|--------------------------------------|---------|---------------|-----------------------|----------------------|---------------------|---------------------|-------------------|-------------------|------------------------|
| | | | | Flow Rate | Cannister | | Grease Hose | Tool & Battery | |
| Model | Battery | Voltage DC | Pressure PSI (Bar) | oz./min. (g/min.) | Capacity oz. (g) | Grease Type NLGI | Length in (mm) | Weight lb (kg) | Size: LxWxH in (mm) |
| LUB5130 | BL2012 | 20 | 6250 (431) | 2.6 (75) | 14 (400) | 2-4 | 30 (762) | 7.2 (3.3) | 19x8x4 (490x200x94) |
| LUB5130 | BL2022 | 20 | 6250 (431) | 2.6 (75) | 14 (400) | 2-4 | 30 (762) | 7.7 (3.5) | 19x8x4 (490x200x94) |



Available in kits

tight spots

| Model | Description |
|-------------|---|
| LUB5130-K12 | 20V Grease Gun, Charger, 1 BL2012 Li-ion Battery & Case |

IQ^{V20} Series[™] LED Task Light

L5110



Ultra-bright white LED casts 180 lumens and lasts up to 20,000 hours



Multi-position head and standing base allow for lighting from above or below

Hanging hook allows versatile positioning at any angle

IQ^{V20} **Series**[™] **intelligent battery management system** provides up to 15 hours from a 3.0 Ah battery and up to 8 hours on a 2.5 Ah battery on a single charge

Ideal for:







Facilities

maintenance

IQ^{V20} Series[™] LED Task Light Tool & Battery Voltage DC Light Output Lumens Head Position Size LxH in (mm) Runtime Model **Battery** Hours L5110 BL2012 20 180 6 13.5 1.81 (.82) 3.4x9.5 (8.6x12.1) L5110 BL2010 180 3.4x9.5 (8.6x12.1) 20 15 2.4 (1.08) 6 L5110 BL2022 20 180 2.4 (1.08) 3.4x9.5 (8.6x12.1) 6



Ingersoll Rand (NYSE:IR) advances the quality of life by creating comfortable, sustainable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a \$12 billion global business committed to a world of sustainable progress and enduring results.









www.ingersollrandproducts.com

Distributed by:

Ingersoll Rand, IR and the IR logo are trademarks of Ingersoll Rand, its subsidiaries and/or affiliates. All other trademarks are the property of their respective owners. Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of products shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request.

Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.