Ingersoll Rand®

2235 Series ½" Impactool™

Industrial/MRO

REAL TOOLS FOR REAL WORK.℠

The bar doesn't raise itself.

The 2235 Series 1/2" Impactool™

A powerful, durable and reliable workhorse whose reputation is built on helping you build yours. It's been rigorously tested, beaten up, dropped and pushed to the limits to make sure it will always work when you need it most. The 2235 Series is incredibly powerful, durable and reliable so that it delivers every time you need REAL WORK done right.

Facility Maintenance

General Industrial

Heavy Equipment Repair

General Automotive

Tool Features

DURABILITY
Born from the legendary durability of the Ingersoll Rand 2135 Series, the 2235 pushes toughness to the next level. It's built with a titanium hammercase, steel-wear plate and composite housing that protect the tool from the harshest environments.

POWER
Punish the toughest bolts with 1,350 ft-lbs. of nut-busting torque and 930 ft-lbs. of max reverse torque powered by Ingersoll Rand's finely tuned twin-hammer impact mechanism. From the most demanding industrial sites to the garage, there is no job that will stand in its way.

Pin drive option available

RELIABILITY
Every component, every mechanism and every function of the 2235 Series has been pushed to the limits to ensure it always performs in the face of the toughest jobs. Backed by a two-year warranty, the 2235 Series is a finely tuned workhorse, from its components to its technology, to be the impact wrench you can always count on to get REAL WORK done.

WEIGHT
At only 4.6 pounds, no other impact wrench on the market can match the combined power and weight of the 2235 Series. With less weighing you down, you can work harder and faster for longer stretches of time.

Optional protective boot prevents external damage and protects from dirt, grime, wear and tear (Part 2235M-BOOT)

Specs

2235 Series 1/2" Impactool™

Model	Drive Size	Retainer Type	Max Torque ft.-lb. (Nm)	Nut-Busting Torque ft.-lb. (Nm)	BPM	Free Speed (rpm)	Weight lb (kg)	Length in. (mm)	Sound Level dB(A)
2235TiMAX	1/2"	Ring	930 (1260)	1350 (1830)	1220	8500	4.6 (2.1)	7.6 (193)	98
2235TiMAX-2	1/2", 2" Ext.	Ring	930 (1260)	1350 (1830)	1220	8500	4.9 (2.2)	9.6 (244)	98
2235PTiMAX	1/2"	Pin	930 (1260)	1350 (1830)	1220	8500	4.6 (2.1)	7.6 (193)	98
2235QTiMAX	1/2"	Ring	900 (1220)	1300 (1760)	1220	8500	4.7 (2.1)	7.6 (193)	88.7
2235QTiMAX-2	1/2", 2" Ext.	Ring	900 (1220)	1300 (1760)	1220	8500	5.0 (2.3)	9.6 (244)	88.7
2235QPTiMAX	1/2"	Pin	900 (1220)	1300 (1760)	1220	8500	4.7 (2.1)	7.6 (193)	88.7

Performance at 90 PSI. Air inlet NPTF 1/4" (6mm). Min hose size 3/8" (10mm). Average air consumption 6 cfm (170l/min)

Ingersoll Rand®

irtools.com/2235

REAL TOOLS FOR REAL WORK.

Ingersoll Rand (NYSE:IR) advances the quality of life by creating and sustaining comfortable and efficient environments. Our people and our family of brands — including Club Car®, Ingersoll Rand®, Thermo King® and Trane® — work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; and increase industrial productivity and efficiency. We are a $13 billion global business committed to a world of sustainable progress and enduring results.

©2016 Ingersoll Rand IRITS–0716-071